






**OBJECT POSITION DETECTOR**

**Patent number:** WO9607981  
**Publication date:** 1996-03-14  
**Inventor:** ALLEN TIMOTHY P (US); GILLESPIE DAVID (US);  
MILLER ROBERT J (US); STEINBACH GUNTER (US)  
**Applicant:** SYNAPTICS INC (US); ALLEN TIMOTHY P (US);  
GILLESPIE DAVID (US); MILLER ROBERT J (US);  
STEINBACH GUNTER (US)  
**Classification:**  
- **international:** G06K11/16  
- **european:** G06F3/033D2G, G06F3/033Z4S2  
**Application number:** WO1995US11180 19950901  
**Priority number(s):** US19940300387 19940902

**Also published as:**

 EP0777888 (A1)  
 EP0777888 (B1)

**Cited documents:**

 US5374787  
 EP0609021  
 EP0574213

**Abstract of WO9607981**

A proximity sensor system includes a sensor matrix array having a characteristic capacitance on horizontal and vertical conductors connected to sensor pads. The capacitance changes as a function of the proximity of an object or objects to the sensor matrix. The change in capacitance of each node in both the X and Y directions of the matrix due to the approach of an object is converted to a set of voltages in the X and Y directions. These voltages are processed by digital circuitry to develop electrical signals representative of the centroid of the profile of the object, i.e., its position in the X and Y dimensions. Noise reduction and background level setting techniques inherently available in the architecture are employed.

